


MD 586 / Veirs Mill Road Bus Rapid Transit Study



**RTS Committee Briefing
November 18, 2014**




Veirs Mill Road Bus Rapid Transit

Agenda

- **Existing Conditions – Roadway and Transit**
- **Project Purpose and Need**
- **Conceptual Alternatives**
- **Preliminary Alternatives Retained for Detailed Study**
- **Typical Sections**
- **Alternative 5B**



Project Location



Veirs Mill Road Bus Rapid Transit


Existing Roadway Conditions

- **6.7-mile corridor**
- **Functional classification: Other principal arterial**
- **Number of lanes: varies from 4 to 6**
- **Intersections:**
 - 20 signalized
 - 26 unsignalized intersections and numerous driveways
- **Average daily traffic: 24,050 to 47,525**
- **Sidewalks with some gaps**
- **No designated bicycle facilities**
- **Metrobus and Ride On bus service**
- **Service roads along much of the corridor**



Veirs Mill Road Bus Rapid Transit

Numerous Typical Sections



Existing Bus Service

- **WMATA's Metrobus**

- Routes Q1, Q2, Q4, Q5, and Q6 on Veirs Mill Road from the Rockville to Wheaton Metrorail Stations
- Route C4 on Veirs Mill Road from Wheaton to Randolph Road
- 11,300 to 12,200 daily riders within study corridor

- **Montgomery County's Ride On**


- Routes 26, 34, 38, 44, and 48 each travel on a segment of Veirs Mill Road within the study corridor
- 4,600 to 6,000 daily riders within the study corridor

- **Bicycle racks mounted on all Metrobus and all Ride On buses**



Veirs Mill Road Bus Rapid Transit

Bus Routes



Purpose and Need

The purpose of the study is to provide a new high-speed, high-efficiency bus line along Veirs Mill Road between the Rockville Metrorail Station and the Wheaton Metrorail Station. The project needs are:

1. System Connectivity
2. Mobility
3. Transit Demand and Attractiveness
4. Livability



Veirs Mill Road Bus Rapid Transit

Future Growth

- Average Daily Traffic (ADT)**

MD 586 Segment	ADT		
	2011 Existing	2040 No-Build	Increase
MD 355 to MD 28	28,800	36,675	27%
MD 28 to Twinbrook Pkwy	33,925	42,300	25%
Twinbrook Pkwy to Aspen Hill Road	47,525	57,775	22%
Aspen Hill Road to Randolph Road	35,100	53,250	52%
Randolph Road to MD 185	37,400	53,900	44%
MD 185 to MD 193	36,350	47,625	31%
MD 193 to MD 97	24,050	32,625	36%

Conceptual Alternatives Overview

- **6 conceptual alternatives – combination of transit service and runningway alternatives**
- **Service Alternatives**
 - No improvements
 - Enhanced Bus Service (Q9)
 - New BRT Service
- **Runningway Alternatives**
 - Shared lanes vs. dedicated lanes
 - Existing lanes vs. re-purpose lanes vs. widening
 - Median-running vs. curb-running



Veirs Mill Road Bus Rapid Transit

Conceptual Alternatives Overview

- **Alternative 1:** No-Build
- **Alternative 2:** TSM/Queue Jumps
- **Alternative 3:** Enhanced bus service in dedicated lanes (where feasible)
- **Alternative 4:** New BRT in all dedicated lanes
- **Alternative 5A:** Reversible BRT in dedicated lane
- **Alternative 5B:** Bi-directional BRT in dedicated lane (with 2 median lanes where feasible)
- **Alternative 6:** New BRT in dedicated lanes and mixed traffic



Veirs Mill Road Bus Rapid Transit

Preliminary Ridership

- Ridership summaries within the study area in 2040:

	Alt 1 (No-Build)	Alt 2 (TSM)	Alt 4C (BRT on ◇)	Alt 4D (All Bus on ◇)
BRT Boardings	0	5,577	9,122	6,902
Other Bus Boardings	29,379	27,213	24,823	27,219
TOTAL BOARDINGS	29,379	32,790	33,945	34,121

- **Some BRT ridership diverts from existing service.**

Slide option 1: I didn't think Gary suggested eliminating this slide, he wanted date added. Joana suggested to eliminate it. Please clarify.



Preliminary Ridership Summary

- **Ridership ranges between:**
 - 5,000 BRT boardings for Alternatives 2 (TSM)
 - 10,000 BRT boardings for Alternative 4 (two lanes entire length)
- **Some BRT ridership diverts from existing service**

Slide Option 2 with reduced ridership data



Preliminary Alternatives Retained for Detailed Study

- **Alternatives Expected to be Retained:**

- 1: No-build
- 2: TSM – Enhanced bus service with Queue Jumps
- 3: New BRT service in dedicated curb lanes (where feasible)
- 5B: New BRT service in bi-directional and 2-lane median sections



Veirs Mill Road Bus Rapid Transit

Preliminary Alternatives Retained for Detailed Study


ALTERNATIVES		Bus Service	New Transit Service					
			Frequency		Span of Service	Speed		Stations/Stops
			Peak	Off Peak		New Services	Existing Metrobus/ Ride-On	Number
No.	Description							
1	No-Build	No Change	10-30 min	15-30 min	all day	NA	No change (10-12 mph)	37 local stops
2	TSM / Intersection Queue Jumps	Enhanced Bus Service - New Express Limited Stop route (similar to proposed Q9 MetroExtra)	12 min	15 min	all day	16 mph	No change (10-12 mph)	37 local stops 11 for Express
3	BRT Service in Dedicated Lanes (where feasible)	New BRT Service	6 min	10 min	all day	18 mph	No change (10-12 mph)	37 local stops 11 BRT stations
5B	Bi-directional BRT in Dedicated Lane + 2-Lane in Median (where feasible)	New BRT Service	6 min	10 min	all day	20 mph	No change (10-12 mph)	37 stops 11 BRT stations



Veirs Mill Road Bus Rapid Transit


Alternative 1

- No-Build
- Existing bus service in existing lanes



Alternative 2


- **TSM/Intersection queue jumps with enhanced bus service**



Veirs Mill Road Bus Rapid Transit

Alternative 3

- **New BRT service in dedicated curb lanes, where feasible**



Veirs Mill Road Bus Rapid Transit

Alternative 5B

- **New BRT service in dedicated bi-directional or two-lane median**


1. West Ends of Study Limits
WESTBOUND EASTBOUND



2. Center of Study Limits
WESTBOUND EASTBOUND



Alternative 5B



Typical Section Treatments

- **Rockville Station to MD 28 → Shared lanes**
 - Not adequate width to accommodate additional lanes due to constrained adjacent land uses.
- **MD 28 to Twinbrook Parkway → Bi-directional lane**
 - Adequate width to accommodate one dedicated transitway lane while minimizing impacts to adjacent residences.
- **Twinbrook Parkway to Newport Mill → Two lanes**
 - Adequate width to accommodate two lanes for majority of section.
- **Newport Mill to Wheaton Station → Shared lanes**
 - Not adequate width to accommodate additional lanes with constrained adjacent land uses.



Veirs Mill Road Bus Rapid Transit

Next Steps / Engineering Methodology

- **Develop detailed horizontal layout**
- **MWCOG runs regional travel demand model to develop refined traffic volumes and BRT ridership**
- **Develop vertical alignments and cross sections to determine limits of disturbance**
- **Analyze traffic and ridership for each alternative**
- **Revise engineering based on ridership traffic analysis**



Veirs Mill Road Bus Rapid Transit

Questions

