



TYPICAL ROAD SECTION

3" BITUMINOUS CONCRETE SURFACE COURSE IN 2-1 1/2" LAYERS
3" BITUMINOUS CONCRETE BASE COURSE
APPROVED SUBGRADE

PAVING SECTION

GENERAL NOTES

1. REFER TO MARYLAND STATE HIGHWAY ADMINISTRATION SPECIFICATIONS FOR MATERIALS AND METHODS OF CONSTRUCTION.
2. THE SLOPE BEHIND THE CURB TOWARD THE ROAD SHALL BE 2% FOR A DISTANCE OF 3' - 0" FROM THE FACE OF CURB.
3. SURFACE AREA OF INLET SLABS SHALL REMAIN ENTIRELY EXPOSED.
4. TOP OF CURB ELEVATION (20' PAVEMENT) = CENTERLINE ELEVATION + 0.11' (FOR 6" CURB HEIGHT)
5. TOP OF CURB ELEVATION (26' PAVEMENT) = CENTERLINE ELEVATION + 0.02' (FOR 6" CURB HEIGHT)

P:\DITSTJ\MCE21003 7-1-94 11:08:00 am EST

APPROVED <u>JAN 5/98</u> DATE	REVISED	MONTGOMERY COUNTY DEPARTMENT OF TRANSPORTATION
<i>Ernie M. ...</i> DIRECTOR, DEPT. OF TRANS.		MODIFIED TERTIARY RESIDENTIAL STREET
<i>Ed ...</i> CHIEF, DIV. OF ENG. SERVICES		STANDARD NO. MC-210.03