



TYPICAL ROAD SECTION  
(OUTSIDE SUBURBAN DISTRICT)

3" BITUMINOUS CONCRETE SURFACE COURSE IN 2 - 1 1/2" LAYERS
5" BITUMUNOUS CONCRETE BASE COURSE
APPROVED SUBGRADE

PAVING SECTION

GENERAL NOTES

1. REFER TO MARYLAND STATE HIGHWAY ADMINISTRATION SPECIFICATIONS FOR MATERIALS AND METHODS OF CONSTRUCTION.
2. SEE STANDARD NO. MC-811.01 - METHODS OF GRADING SIDE SLOPES.
3. THE SIDE DITCH IN FILL SLOPES MAY BE ELIMINATED IN AREAS NOT MASTER PLANNED FOR DEVELOPMENT ONLY AFTER OVERLAND FLOW PATH AND EROSION POTENTIAL ARE CONSIDERED.
4. WHEN SUBGRADE DRAINS ARE REQUIRED, THEY SHALL BE INSTALLED IN ACCORDANCE WITH STANDARD NO. MC-525.01.

P:\JDT\STD\MC21203 6-24-94 8:03:18 am EST

APPROVED <u>JAN 5/96</u> DATE	REVISED	MONTGOMERY COUNTY DEPARTMENT OF TRANSPORTATION
<i>[Signature]</i> DIRECTOR, DEPT. OF TRANS.		PRIMARY RESIDENTIAL ROAD OPEN SECTION
<i>[Signature]</i> CHIEF, DIV. OF ENG. SERVICES		STANDARD NO. MC-212.03