



TYPICAL ROAD SECTION  
(OUTSIDE SUBURBAN DISTRICT)

3" BITUMINOUS CONCRETE SURFACE COURSE IN 2 - 1 1/2 "LAYERS
5" BITUMINOUS CONCRETE BASE COURSE
8" GRADED AGGREGATE BASE COURSE IN 2 - 4" LAYERS *
APPROVED SUBGRADE

PREFERRED

3" BITUMINOUS CONCRETE SURFACE COURSE IN 2 - 1 1/2 "LAYERS
9" BITUMINOUS CONCRETE BASE COURSE IN 2 - 4 1/2" LAYERS *
APPROVED SUBGRADE

ALTERNATE

\* SUBGRADE DRAINS REQUIRED  
SEE MC-525.01

ALTERNATE PAVING SECTIONS

GENERAL NOTES

1. REFER TO MARYLAND STATE HIGHWAY ADMINISTRATION SPECIFICATIONS FOR MATERIALS AND METHODS OF CONSTRUCTION.
2. SEE STANDARD NO. MC-811.01 - METHODS OF GRADING SIDE SLOPES.
3. THE SIDE DITCH IN FILL SLOPES MAY BE ELIMINATED IN AREAS NOT MASTER PLANNED FOR DEVELOPMENT ONLY AFTER OVERLAND FLOW PATH AND EROSION POTENTIAL ARE CONSIDERED.

P:\DDTSTD\MC21302 6-24-94 8:07:15 am EST

APPROVED <u>JAN 5/96</u> DATE	REVISED	MONTGOMERY COUNTY DEPARTMENT OF TRANSPORTATION
<i>John M. ...</i> DIRECTOR, DEPT. OF TRANS.		ARTERIAL ROAD OPEN SECTION
<i>Ed ...</i> CHIEF, DIV. OF ENG. SERVICES		STANDARD NO. MC-213.02