



Montgomery County Department of Permitting Services

255 Rockville Pike, 2nd Floor
 Rockville, MD 20850-4166
 Phone: 311 in Montgomery County or (240)777-0311
 Fax: (240)777-6262
<http://www.montgomerycountymd.gov/permittingservices>



MARYLAND ACCESSIBLE PARKING SPACES

Accessible Parking Spaces for Cars

Accessible parking spaces for cars have at least a 60-inch-wide access aisle located adjacent to the designated parking space. The access aisle is just wide enough to permit a person using a wheelchair to enter or exit the car. Two accessible parking spaces may share a common access aisle. These parking spaces are designated as reserved by a sign showing the symbol of accessibility and a supplemental sign indicating "Maximum Fine \$250" located on level ground not exceeding 1:50 (2%) in all directions. [MCC-Sec. 31-26A(c)]


Van-Accessible Parking Spaces

Van-accessible parking spaces are the same as accessible parking spaces for cars except for three features needed for vans:

1. a wider access aisle (96") to accommodate a wheelchair lift;
2. vertical clearance (98") to accommodate van height at the van parking space, the adjacent access aisle, and on the vehicular route to and from the van-accessible space,
3. an additional sign that identifies the parking spaces as "van accessible."
4. Each van accessible parking space aisle shall have a "No Parking in Access Aisle" sign.

Location

Accessible parking spaces serving a particular building shall be located on the shortest accessible route of travel from adjacent parking to an accessible entrance. In parking facilities that do not serve a particular building, accessible parking shall be located on the shortest accessible route of travel to an accessible pedestrian entrance of the parking facility. In buildings with multiple accessible entrances with adjacent parking, accessible parking spaces shall be dispersed and located closest to the accessible entrances.



Minimum Number of Spaces

Total Number of Parking Spaces Provided (per lot) (i) (ii)	(Column A) Total Minimum Number of Accessible Parking Spaces (60" & 96" aisles)	Van-Accessible Parking Spaces with min. 96" wide access aisle	Accessible Parking Spaces with min. 60" wide access aisle
1 to 25	1	1	0
26 to 50	2	1	1
51 to 75	3	1	2
76 to 100	4	1	3
101 to 150	5	2	3
151 to 200	6	2	4
201 to 300	7	2	5
301 to 400	8	2	6
401 to 500	9	3	6
501 to 1000	2% of total parking provided in each lot	¼ of Column A*	¾ of Column A**
1001 and over	20 plus 1 for each 100 over 1000	¼ of Column A*	¾ of Column A**

*One out of every 4 accessible spaces but not less than one

** 3 out of every 4 accessible parking spaces.

- (i) Outpatient units and facilities: 10 percent of the total number of parking spaces provided serving each such outpatient unit or facility;
 (ii) Units and facilities that specialize in treatment or services for persons with mobility impairments: 20 percent of the total number of parking spaces provided serving each such unit or facility.

VAN ACCESSIBLE PARKING SPACE SIGN
(Required below the reserved parking sign)

*** Increase spacing 50%**

SIGN	DIMENSIONS (INCHES)											
	A	B	C	D	E	F	G	H	J	K	L	
MIN.	12	6	3/8	3/8	1 1/4	1 1/2	1/2	1	1 1/2	2 3/4	4	1 1/2
STD.	18	9	3/8	5/8	2 1/4	2	1	1 1/2	2 3/4	7	1	

COLORS
REGULATORY (COLORS MAY BE REVERSED)
LEGEND: GREEN OR BLACK
BACKGROUND: WHITE (RETROREFLECTIVE)

NO PARKING IN ACCESS AISLE

2 1/2" ARROWHEAD

NOTE: APPROPRIATE ARROW PLATE MAY BE USED WHEN IT IS NECESSARY TO OFFSET INSTALLATION LOCATION DUE TO ACCESS RAMP.

SIGN SIZE	DIMENSIONS (INCHES)										
	A	B	C	D	E	F	G	H	J	K	L
STANDARD	1 1/4	2 1/2	1	2	1 1/2	1 1/2	12	18	6	1 1/4	1 1/2

REFERENCES
MUTCD SECTION - 2B-35
MUTCD SUPPLEMENT - 2B-31

COLORS
LEGEND - RED
BACKGROUND - WHITE

NOTE: ARROW MAY BE REMOVED OR MODIFIED AS NECESSARY

* - SPACING REDUCED 50%

SIGN SIZE	DIMENSIONS (INCHES)							
	A	B	C	D	E*	F	G	H
STD	12	24	3/8	2	2C	1	6	1-3/4

SIGN SIZE	DIMENSIONS (INCHES)								
	J	K	L	M	N	P	Q	R	S
STD	28	3/4	1-1/4	3	1/2	4	3/4	3-1/8	1-1/2

REFERENCES
MUTCD SECTION - 2B-31, 2B-32
MUTCD SUPPLEMENT - 2B-31, 2B-32, 2B-33

COLORS
LEGEND & BORDER - GREEN
WHITE SYMBOL ON BLUE BACKGROUND
BACKGROUND - WHITE

APPROVED: [Signature] DATE: [Date]
DIRECTOR - TRAFFIC & SAFETY

MARYLAND DEPARTMENT OF TRANSPORTATION
State Highway Administration
OFFICE OF TRAFFIC & SAFETY
RESERVED PARKING (HANDICAP SYMBOL)
MAXIMUM FINE \$XXX

Section: SIGNING Standard No. R7-8(5)
Drawn By: _____ Date: _____

SIGN SIZE	DIMENSIONS (INCHES)							
	A	B	C	D	E	F	G	H
STD	12	9	3/8	1-3/4	28	1-1/2	1-1/4	1-1/2

REFERENCES
MUTCD SECTION - NONE
MUTCD SUPPLEMENT - NONE

COLORS
LEGEND - GREEN
BACKGROUND - WHITE

APPROVED: [Signature] DATE: [Date]
DIRECTOR - TRAFFIC & SAFETY

MARYLAND DEPARTMENT OF TRANSPORTATION
State Highway Administration
OFFICE OF TRAFFIC & SAFETY
MAXIMUM FINE \$XXX

Section: SIGNING Standard No. R7-8(3)
Drawn By: _____ Date: _____