



GENERAL NOTES

1. REFER TO MARYLAND STATE HIGHWAY ADMINISTRATION SPECIFICATIONS FOR MATERIALS AND METHODS OF CONSTRUCTION.
2. CURB TO BE MARYLAND STATE HIGHWAY ADMINISTRATION TYPE SN OR BF BITUMINOUS CONCRETE.
3. THIS STANDARD IS INTENDED TO BE USED IN TEMPORARY SITUATIONS ONLY.
4. BACK OF CURB TO BE LOCATED 6 INCHES MINIMUM INSIDE EDGE OF PAVING.
5. APPLY TACK COAT WHEN PLACED ON EXISTING PAVEMENT.

P:\DITSTJ\MC10301 6-24-94 6:44:54 am EST

APPROVED <u>JAN 5/95</u> <small>DATE</small>	REVISED <hr/> <hr/> <hr/> <hr/> <hr/> <hr/> <hr/> <hr/>	MONTGOMERY COUNTY DEPARTMENT OF TRANSPORTATION
<i>Gabary M. ...</i> DIRECTOR, DEPT. OF TRANS.		BITUMINOUS CONCRETE CURB
<i>Ed ...</i> CHIEF, DIV. OF ENG. SERVICES		STANDARD NO. MC-103.01