



### GENERAL NOTES

1. REFER TO MONTGOMERY COUNTY DEPARTMENT OF TRANSPORTATION SPECIFICATIONS FOR MATERIALS, METHODS OF CONSTRUCTION, AND EXPANSION JOINT LOCATIONS.
2. MOUNTABLE CURB SHALL ONLY BE USED ON TERTIARY STREETS OR ON SECONDARY RESIDENTIAL CUL-DE-SACS 500 FEET OR LESS IN LENGTH, MEASURED FROM THE LAST INTERSECTING STREET.
3. WHENEVER STANDARD MC-100.01 IS USED IN CONJUNCTION WITH THIS STANDARD, A TEN FOOT TRANSITION SHALL BE PROVIDED FROM STANDARD MC-104.01 TO STANDARD MC-100.01 FOR CURB RETURNS AND CURB SECTIONS WHICH INCLUDE INLETS.
4. TRANSITION BETWEEN STANDARD MC-104.01 AND MC-100.01 OR MC-101.01 SHALL BE ACCOMPLISHED HOLDING THE FLOW LINE SLOPE CONSTANT.
5. THE STANDARD DISTANCE BETWEEN JOINTS SHALL BE TEN FEET (MAXIMUM AND MINIMUM DISTANCES SHALL BE THIRTEEN FEET AND FIVE FEET RESPECTIVELY).
6. EXPANSION JOINT MATERIAL SHALL BE 1/2 INCH PREFORMED CORK, TRIMMED AND SEALED WITH NON-STAINING TWO-COMPONENT POLYSULFIDE OR POLYURETHANE ELASTOMERIC TYPE SEALANT COMPLYING COMPLYING WITH ASTM-C920. 

<p>APPROVED <u>14 APR 06</u> DATE</p> <p><i>Ante G. Holt</i> DIRECTOR, DEPT. OF PUBLIC WORKS &amp; TRANSPORTATION</p> <p><i>Holger Serrano</i> for CHIEF, DIV. OF CAP. DEV.</p>	<p>REVISED</p> <p> ASTM-C920 4/2005</p>	<p>MONTGOMERY COUNTY DEPARTMENT OF PUBLIC WORKS &amp; TRANSPORTATION</p> <p><b>MOUNTABLE CONCRETE CURB AND GUTTER TYPE F</b></p> <p><b>STANDARD NO. MC-104.01</b></p>
---	--	---