



GENERAL NOTES

1. REFER TO MARYLAND STATE HIGHWAY ADMINISTRATION SPECIFICATIONS FOR MATERIALS AND METHODS OF CONSTRUCTION.
2. EXPANSION JOINT MATERIAL SHALL BE 1/2 INCH PREFORMED CORK, TRIMMED AND SEALED WITH NON-STAINING, TWO COMPONENT POLYSULFIDE OR POLYURETHANE ELASTOMERIC TYPE SEALANT, COMPLYING WITH ASTM-C920. ¹
3. SCORE THE CONCRETE FOR THE TRANSVERSE JOINTS TO A DEPTH OF 1/3 OF THE THICKNESS TO PROVIDE A WEAKENED PLANE.
4. THE WIDTH MAY BE INCREASED TO MATCH THE WIDTH OF AN APPROACHING BIKEWAY.

<p>APPROVED <u>14 APR 06</u> DATE</p> <p><i>Anth Hoff</i> DIRECTOR, DEPT. OF PUBLIC WORKS & TRANSPORTATION</p> <p><i>Holger Senarum</i> for CHIEF, DIV. OF CAP. DEV.</p>	<p>REVISED</p> <p>¹ ASTM-C920 4/2006</p>	<p>MONTGOMERY COUNTY DEPARTMENT OF PUBLIC WORKS & TRANSPORTATION</p> <p>MEDIAN OPENING</p> <p>STANDARD NO. MC-114.01</p>
--	---	--