



TYPICAL ROAD SECTION

3" BITUMINOUS CONCRETE SURFACE COURSE IN 2 - 1 1/2" LAYERS
3" BITUMINOUS CONCRETE BASE COURSE
APPROVED SUBGRADE

PAVING SECTION

GENERAL NOTES

1. REFER TO MARYLAND STATE HIGHWAY ADMINISTRATION SPECIFICATIONS FOR MATERIALS AND METHODS OF CONSTRUCTION.
2. SEE STANDARD NO. MC-811.01 - METHODS OF GRADING SIDE SLOPES.
3. TOP OF CURB ELEVATION = CENTERLINE ELEVATION + 0.02' (FOR 6" CURB HEIGHT).
4. SIDEWALK SHALL BE REQUIRED ON ONE SIDE ONLY FOR STREETS LONGER THAN 300'.
5. WHEN A TRAFFIC BARRIER IS WARRANTED INCREASE THE RIGHT OF WAY TO ALLOW THE TRAFFIC BARRIER TO BE PLACED OUTSIDE OF THE SIDEWALK.

P:\DIT\STD\MC21002 9-28-95 2:12:12 PM EST

APPROVED <u>JAN 5/96</u> DATE	REVISED	MONTGOMERY COUNTY DEPARTMENT OF TRANSPORTATION
<i>Julius M. Mader</i> DIRECTOR, DEPT. OF TRANS.		TERTIARY RESIDENTIAL STREET 50' RIGHT-OF-WAY
<i>Edgar Gonzalez</i> CHIEF, DIV. OF ENG. SERVICES		STANDARD NO. MC-210.02