



TYPICAL ROAD SECTION

3" BITUMINOUS CONCRETE SURFACE COURSE IN 2 - 1 1/2" LAYERS
5" BITUMINOUS CONCRETE BASE COURSE
APPROVED SUBGRADE

PAVING SECTION

GENERAL NOTES

1. REFER TO MARYLAND STATE HIGHWAY ADMINISTRATION SPECIFICATIONS FOR MATERIALS AND METHODS OF CONSTRUCTION.
2. SEE STANDARD NO. MC-811.01 - METHODS OF GRADING SIDE SLOPES.
3. TOP OF CURB ELEVATION = CENTERLINE ELEVATION -0.13' (FOR 6" CURB HEIGHT) .
4. BIKE PATH SHALL BE REQUIRED ONLY IF SPECIFIED IN MASTER PLAN.
5. WHEN A TRAFFIC BARRIER IS WARRANTED HOLD A MINIMUM OF 7'-0" GREEN SPACE BETWEEN THE CURB AND THE SIDEWALK.

P:\DOT\STD\NC21201 6-24-94 7:59:37 am EST

APPROVED <u>JAN 5/96</u> DATE	REVISED	MONTGOMERY COUNTY DEPARTMENT OF TRANSPORTATION
<i>Lesley Mata</i> DIRECTOR, DEPT. OF TRANS.		PRIMARY RESIDENTIAL ROAD
<i>Edyabouzel</i> CHIEF, DIV. OF ENG. SERVICES		STANDARD NO. MC-212.01