



TYPICAL ROAD SECTION

3" BITUMINOUS CONCRETE SURFACE COURSE IN 2 - 1 1/2" LAYERS
7" BITUMINOUS CONCRETE BASE COURSE
8" GRADED AGGREGATE BASE COURSE IN 2 LAYERS
*
APPROVED SUBGRADE

PREFERRED

3" BITUMINOUS CONCRETE SURFACE COURSE IN 2 - 1 1/2" LAYERS
9" BITUMINOUS CONCRETE BASE COURSE IN 2 - 4 1/2" LAYERS
4" GRADED AGGREGATE BASE COURSE
*
APPROVED SUBGRADE

ALTERNATE

* SUBGRADE DRAINS REQUIRED SEE MC-525.01

PAVING SECTIONS

GENERAL NOTES

1. REFER TO MARYLAND STATE HIGHWAY ADMINISTRATION SPECIFICATIONS FOR MATERIALS AND METHODS OF CONSTRUCTION.
2. TOP OF CURB ELEVATION = CENTERLINE ELEVATION -0.34' (FOR 6" CURB HEIGHT) .

P:\DDTST\DMC21401 6-24-94 82338 am EST

APPROVED <u>JAN 5/96</u> DATE	REVISED	MONTGOMERY COUNTY DEPARTMENT OF TRANSPORTATION
<i>[Signature]</i> DIRECTOR, DEPT. OF TRANS.		COMMERCIAL-BUSINESS DISTRICT ROAD
<i>[Signature]</i> CHIEF, DIV. OF ENG. SERVICES		STANDARD NO. MC-214.01