



GENERAL NOTES

1. THIS STANDARD MAY BE USED ONLY WITH THE PRIOR APPROVAL OF MCDOT AT THE PRELIMINARY PLAN STAGE.
2. THIS STANDARD IS APPLICABLE TO INTERSECTIONS OF TERTIARY, SECONDARY AND PRIMARY ROADS WITH OTHER TERTIARY, SECONDARY OR PRIMARY ROADS. IT IS NOT APPLICABLE TO ROADS WITHOUT CURB AND GUTTER.
3. THE NEAREST POINT OF ANY DRIVEWAY APRON EXTENSIONS SHALL NOT BE LOCATED WITHIN 25' OF THE POINT OF CURVATURE OF CURB AND GUTTER AT THE INTERSECTION.
4. MCDOT STANDARD MC-100.01 CURB AND GUTTER MUST BE USED WITHIN THE LIMITS OF THE CIRCLE, INSIDE RADIUS AND OUTSIDE RADIUS TO THE POINT OF CURVATURE OF CURB AND GUTTER ON THE CONNECTING STREETS. USE A 1% MINIMUM GUTTER GRADE EXCEPT AROUND THE ISLAND.
5. STREET TREE PLANTINGS SHALL BE IN ACCORDANCE WITH MCDOT STANDARD MC-830.01.
6. SIDEWALKS SHALL BE PROVIDED IN ACCORDANCE WITH THE APPLICABLE ROAD STANDARDS AND STANDARD MC-112.01 FOR RESIDENTIAL SIDEWALK RAMP. THE SIDEWALK SHALL EXTEND ALONG THE INTERSECTION TRUNCATION, ONE FOOT FROM THE PROPERTY LINE. SIDEWALK RAMP (8 TOTAL) SHALL BE LOCATED AT THE END OF EACH CURB TANGENT ON EACH LEG OF THE INTERSECTION.

P:\DOT\STD\MC22102 6-24-94 850:30 am EST

APPROVED <u>JAN 5/96</u> DATE	REVISED <hr/> <hr/> <hr/> <hr/> <hr/> <hr/> <hr/> <hr/>	MONTGOMERY COUNTY DEPARTMENT OF TRANSPORTATION
 DIRECTOR, DEPT. OF TRANS.		TRAFFIC CONTROL CIRCLE RESIDENTIAL ROADS
 CHIEF DIV. OF ENG. SERVICES		STANDARD NO. MC-221.02