



GENERAL NOTES

1. REFER TO MARYLAND STATE HIGHWAY ADMINISTRATION SPECIFICATIONS FOR MATERIALS AND METHODS OF CONSTRUCTION.
2. DRIVEWAY APRON TO BE MAINTAINED BY PROPERTY OWNER.
3. CONCRETE APRONS SHALL BE USED WHEN CONCRETE SIDEWALK IS CONSTRUCTED.
4. CONCRETE APRONS SHALL BE SEVEN INCH MINIMUM THICKNESS WITH EXPANSION/CONTRACTION JOINTS PER MC-301.01.
5. THIS STANDARD SHALL BE USED WITH MC-101.01 OR MC-102.01 CURB AND GUTTER ONLY.
6. WINGS CAN VARY 0' TO 5', HOWEVER THEY MUST BE SYMETRICAL ON BOTH SIDES.
7. EXPANSION JOINT MATERIAL SHALL BE 1/2 INCH PREFORMED CORK, TRIMMED AND SEALED WITH NON- STAINING TWO-COMPONENT POLYSULFIDE OR POLYURETHANE ELASTOMERIC TYPE SEALANT COMPLYING WITH ASTM-C920. 1

APPROVED <u>14 APR '06</u> DATE	REVISED 1 ASTM-C920 4/2006	MONTGOMERY COUNTY DEPARTMENT OF TRANSPORTATION
 DIRECTOR, DEPT. OF TRANS.		TERTIARY DRIVEWAY
 CHIEF, DIV. OF CAP. DEV.		STANDARD NO. MC-300.01