


GENERAL NOTES

1. REFER TO MARYLAND STATE HIGHWAY ADMINISTRATION SPECIFICATIONS FOR MATERIALS AND METHODS OF CONSTRUCTION.
2. THIS STANDARD IS INTENDED TO BE USED FOR REPLACEMENT OF EXISTING WOODEN POSTS.
3. BARRICADE POST IS TO BE PLACED IN AN AUGERED HOLE SPACED 5 FEET ON CENTER.
4. REFLECTORIZED METAL PLATE TO BE FASTENED 6 INCHES BELOW THE TOP FACE (FRONT SIDE) OF THE POST (4" MIN. WIDTH, 70 SQ. IN. MINIMUM AREA) USING GALVANIZED SCREWS.

P:\DITSTD\MCB0001: 6-24-94 9:44:21 am EST

APPROVED <u>JAN 5/95</u> <small>DATE</small>	REVISED <hr/> <hr/> <hr/> <hr/> <hr/> <hr/> <hr/> <hr/>	MONTGOMERY COUNTY DEPARTMENT OF TRANSPORTATION
 DIRECTOR, DEPT. OF TRANS.		BARRICADE POST
 CHIEF, DIV. OF ENG. SERVICES		STANDARD NO. MC-800.01