

W20-1  
48" x 48"



W20-4  
48" x 48"



W20-7a(1)  
48" x 48"



BUFFER

NOTE: ACCESS POINTS WITHIN LANE CLOSURE  
SHALL BE CONTROLLED BY FLAGGER(S)

REFER TO TCP 100.01 FOR SIGN  
SPACING, TAPER LENGTHS AND  
BUFFER ZONE LENGTHS

WORK AREA

BUFFER

50'-100'

W20-7a(1)  
48" x 48"

W20-4  
48" x 48"

W20-1  
48" x 48"

← DIRECTION OF TRAFFIC

—●— SIGN

▨ WORK SITE

● FLAGGER

○ TRAFFIC DRUMS  
OR CONES

S<sup>1</sup>=30 FT.

S<sup>2</sup>=10 FT.

DY CL

REVISION BY	DATE	APPROVED

DATE	TRAFFIC OPERATIONS SECTION MONTGOMERY COUNTY, MARYLAND	
DES. BY		
MCDPW/T	FLAGGING CONTROL NON - INTERSECTION	
DRAWN BY		
TCLE	APPROVED _____ CHIEF, TRAFFIC OPERATIONS SECTION	
SCALE		
NTS	STANDARD TCP-102.02      — OF — SHEETS	