

W20-1
48" x 48"



W20-4
48" x 48"



W20-7a(1)
48" x 48"



C

B

A

BUFFER

NOTE: ACCESS POINTS WITHIN LANE CLOSURE SHALL BE CONTROLLED BY FLAGGER(S)

REFER TO TCP 100.01 FOR SIGN SPACING, TAPER LENGTHS AND BUFFER LENGTHS

50' TO 100'

WORK AREA

BUFFER

50' TO 100'

A

B

C

W20-7a(1)
48" x 48"



W20-4
48" x 48"



W20-1
48" x 48"



DY CL

B

A

BUFFER



W20-1
48" x 48"



W20-7a(1)
48" x 48"

DY CL

DIRECTION OF TRAFFIC

SIGN

WORK SITE

FLAGGER

TRAFFIC DRUMS OR CONES

S¹ = 30 FT.

S² = 10 FT.

REVISION BY	DATE	APPROVED

DATE	07-01-14
DES. BY	MCDPWT
DRAWN BY	TCLE
SCALE	NTS
TRAFFIC OPERATIONS SECTION MONTGOMERY COUNTY, MARYLAND	
FLAGGING CONTROL AT 3 - LEG INTERSECTION FAR - SIDE CLOSURE	
APPROVED _____ CHIEF, TRAFFIC OPERATIONS SECTION	
STANDARD TCP-105.07 _____ OF _____ SHEETS	