



2425 Reedie Drive, 7th Floor Wheaton, MD 20902 240-777-0311 montgomerycountymd.gov/dps

Section 4.4.7. Residential - 200 Zone (R-200) Standard Method Development Standards.

For Guidance Only

Zone		R-200	
		Residential, one-family, detached.	
Area Requirement		Minimum lot size 20,000) sq. ft.
Maximum Coverage		25% including accessory buildings.	
		See Page 2 for infill development & lot coverage.	
Minimum Front Setback		40 ft. or established building line (EBL), whichever is greater. EBL is not required for additions, only for new one-family dwellings. ²	
Minimum Side Setback		Total 25 ft.; one side 12 ft. ¹	
Minimum Side Street Setback		Abutting lot fronts on the side street and is in a Residential Detached Zone 40 ft Abutting lot does not front on the side street or is not in a Residential Detached Zone 15 ft.	
Minimum Rear Setback		30 ft.	
Minimum Lot Frontage		100 ft. at front building line. 25 ft. at street line.	
Maximum Building Height		50 ft. if lot area is 40,000 square feet or more, otherwise see chart :	
Lot Area in Square Feet		Height in Feet	
equal to or greater than	and less than	height to highest point of any roof	Mean height btw. eaves and ridge of gable, hip, mansard, gambrel roof
25,000	40,000	45 or	40
15,000	25,000	40 or	35
0	15,000	35 or	30
Accessory Buildings The footprint of an accessory building must not exceed 50% of the footprint of the main building (one-family detached dwelling) or 600 sq/ft whichever is greater. This limit does not apply to a building accessory to an agricultural use.		 Rear yard only. 35 ft. maximum height, measured to the highest point of roof surface. 65 ft. Front setback 40 ft. Side Street Setback, abutting lot fronts on the side street and is in a residential detached zone. 15 ft. Side Street Setback, abutting lot does not front on the side street or is not in a residential detached zone. 12 ft. Side Setback (all lots except corner lots) 12 ft. Rear on a Corner lot where abutting lot fronts on the side street and is in a residential detached zone 7 ft. Rear Setback, if not otherwise addressed 	
Remarks		² See <u>Established Building Line Methods</u> on DPS website.	



DPS | Montgomery County Department of Permitting Services



255 Rockville Pike, 2nd Floor Rockville, MD 20850-4166

Phone: 311 in Montgomery County or (240)777-0311

Fax: (240)777-6262

http://www.montgomerycountymd.gov/permittingservices

Section 4.4.7. Residential - 200 Zone (R-200) Standard Method Development Standards.

INFILL DEVELOPMENT Maximum Coverage For Infill Development Lots Your project is considered infill development if the following apply: The lot was created: Lot area less than 30% -By a plat recorded before January 1, 1978; or 6000 sa.ft. -By a plat of resubdivision that created fewer than 6 lots from a lot previously created by a plat recorded 30%, minus .001 multiplied by the square foot Lot area equal to or before January 1, 1978; greater than 6000 of lot area over 6000 sq.ft. -the lot is less than 25,000 square feet in area AND sa.ft. but less than See **EXAMPLE** below 16,000 sq.ft. The construction proposed is: -A new detached house. OR -demolition is more than 50% of the existing floor area of all floors of the dwelling; OR 20% Lot area equal to or -addition is more than 50% of the existing floor area greater than 16,000 of all floors of the dwelling. sq.ft. INFILL DEVELOPMENT LOT **COVERAGE**- definition: **EXAMPLE:**

Area that may be covered by any building, including any accessory building, and any weather-proofed floor area above a porch. This does not include any bay window, chimney, porch, or up to 240 sq.ft. of a detached garage if it is less than 350 sq.ft. of floor area and less than 20 ft. in height.

Your lot size is 9458 sq. ft. - 6000 sq. ft. Minus Equals 3458 sq. ft. Multiply times .001

Equals 3.45 percent Base Coverage 30.00 percent Minus 3.45 percent 26.55 percent Equals

This is the new maximum amount of lot coverage for this lot.